

-4001

0

TIME [x50 μ s]


-400

-400


TIME [x50 μ s]

TIME [$x50 \mu s$]






DETECTED WAVEFORMS UNDER BASIC WELDING CONDITIONS



DETECTED WAVEFORMS UNDER BASIC WELDING CONDITIONS





FREQ. CHARACTERISTICS OF YH

段 送信元-MIYOSI&MIYCSI





FIG.13








FIG.15

TABLE-1

		UPPER SHEET t ₁		
	LOWER/UPPER	0.8mm	1.0mm	1.2mm
LOWER SHEET t ₂	0.8mm	3.5m/min.	3.5m/min.	3.5m/min.
	"	4.0m/min.		
	"	4.5m/min.		
	"	5.0m/min.		
	1.0mm	3.5m/min.		
	1.2mm	3.0m/min.		
	"	3.5m/min.		3.5m/min.
	"	4.0m/min.		

宛先-FOLEY

2002-02-25 19:16

FIG.16






FIG.17










FIG.19



16/20






FIG.22




FIG.23





FIG.24



BEAD LENGTH 30mm

DIVIDED

NON-WELDED CONFORMING

CONFORMING PROPORTION = CONFORMING LENGTH 6mm × 3 SUB-SECTIONS
TOTAL WELD LENGTH 30mm = 0.6

FIG.26

